



Axiom Technologies, LLC

255 Pennbriht Dr., Suite 220
Houston, Texas 77090

Tel: (281) 931-0907

Fax: (281) 931-6562

www.axiomsafety.com

XH2, Self-Contained Hydraulic Control Panel



- Zero Leakage
- Provides a local source of hydraulic pressure up to 3000 psi
- The manual pump design means no external power is required
- Continuously energized failsafe solenoid - Can accommodate customer's solenoid of choice
- Hydraulic interface for fire loops and manual shutdown
- Simple hydraulic circuit and high quality components insure high reliability
- Very low maintenance
- Low cost, simple to install
- Two year limited warranty

The XH2 is built to the same standards as all Axiom self-contained products, with thousands of installed units providing reliable service

- Components rated to operate from -40 °C to +85°C ambient temperature.
- Environmentally friendly. The hydraulic circuits are enclosed in an aluminum box that holds any oil leakage to prevent ground contamination.
- All components accessible - easy maintenance.
- Intruder protection. The enclosure may be pad-locked to prevent unauthorized access to the internal components.
- No sliding seals means no risk of the device failing because of lubricants drying out, no need for periodic disassembling, cleaning and lubricating.
- Low pressure pilot circuit ensures that the hydraulic circuits are leak free even if operating with low-viscosity hydraulic fluids



Axiom Technologies, LLC

255 Pennbriht Dr., Suite 220
Houston, Texas 77090

Tel: (281) 931-0907

Fax: (281) 931-6562

www.axiomsafety.com

XH2-Hydraulic Panel Typical Application

